





Congratulations on your purchase of this high quality product from Voda Plumbingware. Please read the following before installation and retain (along with your receipt) for future reference.

## **TECHNICAL SPECIFICATIONS**

### **Suitable for All Pressures**

Minimum Pressure = 17kPa

Maximum operating Pressure = 500kPa\* (As per NZ Building Code AS/NZ 3500.1)

Maximum operating Temperature = 65 deg. Celsius

For domestic use only.

# **CONFIGURATION**

Mains Pressure systems Remove the aerator insert from

> the housing and change to the mains pressure insert supplied.

See diagram.

Unequal Low systems Install as supplied.

Equal Low systems Install as supplied.

## **INSTALLATION**

FOR PRESSURES EXCEEDING 500kPa INSTALL A PRESSURE REDUCING VALVE. THOROUGHLY FLUSH ALL PIPES TO ELIMINATE ANY REMAINING DIRT AND RESIDUE AND INSTALL INLINE FILTERS. FAILURE TO DO SO MAY VOID THE WARRANTY.

- Spout-**Mounting Nut** Handle Back-nut Offset Mounting washer Rubber **Changing Aerator for** Aerator **Mains Pressure only** Insert Aerator Housing
- Fit offsets and body to wall mounted wing backs and adjust width to match the faucet body back-nuts. NB: It is essential to apply either Teflon sealing tape or graphite & hemp around the screwed tube prior to installation.
- Fit mounting washers to the faucet body back-nuts and tighten back-nuts on to offsets. NB: Do not over-tighten - no thread tape is required.

ATTACH PROOF OF PURCHASE HERE

- Fit the centre spout. Push spout onto faucet body, be careful not to push past split collar. Mounting nut should be tightened down with adjustable spanner.
- Turn on mains supply. Check for leaks

### **WARRANTY**

## PLEASE CALL US BEFORE REMOVING SLIDE SHOWER OR UNDERTAKING ANY REPAIR WORK.

Please refer to our website for warranty information: www.vodaplumbingware.co.nz/warranty

In the unlikely event that this product fails during its warranty period, phone our Customer Service team immediately on 0508 367 366 – as unauthorised removal of the product may void the warranty.

### CARE AND MAINTENANCE

# SHOULD NOT BE CLEANED WITH ACIDIC, CAUSTIC/ALKALINE, ABRASIVE OR CITRIC CLEANERS.

A soft, damp cloth is recommended for cleaning (Not a Micro fibre cloth). Mild soap solutions can also be used on occasion. See website for full care instructions: www.vodaplumbingware.co.nz/tapware-care-instructions/